

LENOX BRUSHED GOLD TONE COMMERCIAL AUTOMATIC SENSOR FAUCET SPECS




Product Details

- Durable Vandal-Resistant Brass Body; Ideal for Residential as well as commercial high use applications
- Intelligent: with its microcomputer controlling its action, the faucet will self-adjust its best detection zone as per the color and shape of lavatory
- Flashing light indicator; a diagnostic indicators for power up, low battery, and solenoid function.
- Meaning of the codes are described in the installation instructions.
- Convenient to maintain: with built-in strainer to prevent sundries from entering the solenoid valve and the strainer is easy to clean

Other Details

Product Details



Specs:

Power: DC:6V(4AA alkaline

battery)

AC:220V-240V; 50/60HZ

Water Consumption: 0.05Mpa-

0.6Mpa

Detection Zone: 16-32 cm or

adiustable

Motor valve lifespan: up to

500000 flushes

Battery lifespan: 100000 cycles

Static Power Consumption: 0.36mw

Working Power consumption:

0.5mw

Inductive Opening Time: < 1

second

Inductive Closing Time: < 2

second

Dia.of inlet / outlet pipe:

G1/2"

Flux: ≥0.07L/S

Temperature: 0.1-50°/C Water Pressure: 0.05Mpa -

0.7Mpa

